



Laminato a freddo /
Cold-rolled steel

LAMINATI A FREDDO LUCIDI COLD-ROLLED STEEL

	Min	Max
Gamma spessori / Range of thicknesses	0.35 mm	3 mm
Gamma larghezze / Range of widths	600 mm	2000 mm

Qualità e norme di riferimento / Quality and reference standards

EN 10130	EN 10209	EN 10268	EN 10139*					
DC01	DC01EK	HC260LA	DP 600	DC01	DC03	DC04	DC05	DC06
DC03	DC04EK	HC300LA	-	A	A	A	LC	LC
				LC	LC	LC		
DC04	DC06EK	HC340LA	-	C290	C290	C290	-	-
DC05	DC03ED	HC380LA	-	C340	C340	C340	-	-
DC06	DC04ED	HC420LA	-	C390	C390	C390	-	-
DC07	DC06ED	-	-	C440	C440	C440	-	-
-	-	-	-	C590	C590	C590	-	-
-	-	-	-	C690	-	-	-	-



RIVESTITI: ZINCATO HOT DIP GALVANIZED

	Min	Max
Gamma spessori / Range of thicknesses	0.4 mm	4 mm
Gamma larghezze / Range of widths	600 mm	1800 mm

Qualità e norme di riferimento / Quality and reference standards

EN 10346	EN 10346	EN 10346
DX51D	S220GD	HX260LAD
DX52D	S250GD	HX300LAD
DX53D	S280GD	HX340LAD
DX54D	S320GD	HX380LAD
DX56D	S350GD	HX420LAD
DX57D	S550GD	HX460LAD
-	-	HX500LAD



Rivestiti zincato /
Galvanized steel

